



TECHNICAL DATA

102 Barton Street, St. Louis MO 63104
Ph: 800-325-9962 / Fax: 314-865-4107
www.schaefferoil.com



4002 BED RELEASE AGENT

Bed Release Agent is an environmentally friendly specially formulated water mixable type product that is designed to provide clean, rapid and easy separation of asphalt, concrete, dirt, gravel, etc., from the beds of haul trucks and dump trucks.

Unlike diesel fuel, water-soluble oils, vegetable oils and various soaps that are commonly used as release agents, Bed Release Agent, when applied, provides the following performance benefits:

- Formation of an interfacial film which promotes rapid and complete separation of the load from the bed of the truck.
- Prevention of the buildup of deposits on the bed.
- Partial biodegradability. Bed Release Agent contains components that are biodegradable, thus minimizing environmental concerns associated with spillage of any residual product onto the ground during unloading.
- High natural flash point. This results in the minimization of fire hazards associated with hot loads.
- Economical to use.
- Low V.O.C. content.

Application and Dilution Rate:

For most applications: use one gallon of Bed Release Agent to 30 gallons of water.

For Super Pave or heavy polymer asphalts: use one gallon of Bed Release Agent to 15 gallons of water.

Apply one gallon of the total mixture onto entire bed of truck before each load. Bed Release Agent can be sprayed onto the bed of the truck using conventional spraying equipment.

TYPICAL PROPERTIES

Specific Gravity	0.8767
Flash Point °F/°C (ASTM D-92)	270°/132.22°