



**SPECIALIZED LUBRICANTS**

---

**1. Substance/Product Identification**

**Product Name: 137CTPW Carbon Treat Premium Winter**

**Company/Address: Schaeffer Mfg  
102 Barton Street  
Saint Louis, Missouri 63104  
USA**

**Synonyms:**

**Preparation/Revision Date: 03/16/2011**

**Product Use/Type: Fuel additive for diesel and biodiesel fuels**

**Emergency Phone Number: +1 314 865-4105 (24-hour response number)  
+ 1 314 865-4100 (Business hours 8:30AM-5:00PM)  
1-800-325-9962 (US & Canada)**

**Website: [www.schaefferoil.com](http://www.schaefferoil.com)**

**MSDS Number: 137CTPW Version 1.0**

**2. Hazards Identification**

**Appearance: Tan to dark color**

**Odor: Aromatic solvent odor**

**Signal Word: Danger**

**Principal Hazards: Flammable. May be harmful by inhalation and enters airways. Causes skin and severe eye irritation. Contains components that are suspected of causing cancer. Toxic to aquatic life with long lasting effects**

**Hazardous Materials Information System  
(U.S.A)**

**Health: 2  
Fire: 2  
Reactivity: 1**

**National Fire Protection Agency System  
(U.S.A.)**

**Health: 2  
Fire: 2  
Reactivity: 1**

See Section 11 for complete health hazard information

**Product Name: 137CTPW Carbon Treat Premium Winter**

**3. Composition and Information on Ingredients**

**Hazardous Ingredients**

<b>Ingredient Name</b>	<b>CAS No.</b>	<b>EU Number</b>	<b>Percentage (by wt.)</b>
Heavy Aromatic (petroleum) solvent Naphtha	64742-94-5	265-198-5	4 – 10.5
Naphthalene	91-20-3	202-049-5	0.4 – 0.9
2-Ethylhexyl Nitrate	27247-96-7	248-363-6	1 – 10
2-Butoxyethanol	111-76-2	203-905-0	1 – 5
1,2,4-Trimethylbenzene	95-63-6	202-436-9	4 – 10.5
Light Aromatic (petroleum) solvent Naphtha	64742-96-6	265-199-0	10 – 21
Xylene	1330-20-7	215-535-7	4 - 7
Petroleum Distillate	64742-47-8	265-149-8	25 – 40
Ethylbenzene	100-41-4	202-849-4	2 – 5
Light Ends of Polyethylenebenzene Residue	178535-25-6		6 – 14
Vinyl Acetate	108-05-4	203-545-4	0.02 – 0.3



**Symbols:**

## Product Name: 137CTPW Carbon Treat Premium Winter

### 4. First Aid Measures

**Ingestion:** If swallowed do not induce vomiting. Allow victim to rinse mouth and then drink 2 to 4 glasses of water. Never give anything by mouth to an unconscious person. Seek medical attention immediately.

**Eyes:** Flush eyes with eyelids open with clear, clean water for 15 minutes. Seek medical attention immediately

**Inhalation:** Remove to fresh air. If not breathing give artificial respiration. If breathing is difficult administer oxygen.

**Skin:** Immediately wash with soap and water. Rinse thoroughly. If irritation develops or persists seek medical attention immediately.

**Additional Information: Note to Physician:** Activated charcoal mixture may be administered. To prepare activated charcoal mixture, suspend 50 grams activated charcoal in 400 ml water and mix thoroughly. Administer 5ml/kg or 350 ml for an average adult.

Because of the danger of aspiration, emesis or gastric lavage should not be employed unless the risk is justified by the presence of additional toxic additives. Activated charcoal may induce vomiting, but may be given after emesis or lavage to absorb toxic additives. Steroid therapy in mild to moderate cases does not improve outcome. Bacterial pneumonia often occurs after exposure, but prophylactic antibiotics are not indicated and should be reserved for documented bacterial pneumonia.

### 5. Fire Fighting Measures:

**Flash Point:** 122°F (50°C) PMCC ASTM D-93

**Extinguishing Media:** Carbon dioxide foam, dry chemical foam, sand, earth, water-fog

**Firefighting Procedures:** Evacuate personnel to a safe area. Wear self-contained breathing apparatus. Cool tank/containers with water spray. Fight fire from maximum distance, use extreme caution as heat may decompose material and rupture containers.

**Unusual Fire & Explosion:** Vapors may be heavier than air and travel along the ground to a distant ignition source and flash back. Containers may rupture upon heating. The 2-Ethylhexyl Nitrate contained in this product may undergo a self-accelerating exothermic reaction if the product is heated above 212°F (100°C).

**Hazards:** Hazardous gases or vapors produced in fire are carbon monoxide and oxides of nitrogen. There is a risk of explosion if heated under confinement.

**Product Name: 137CTPW Carbon Treat Premium Winter**

## **6. Accidental Release Measures**

**Spill Procedures and Clean up methods:** Eliminate all sources of ignition. Absorb spills with absorbent clay or other absorbent material. Ventilate confined spaces. Dike spill to keep out of sewers, waterways and watercourses. Collect used absorbent material and discard as dictated by National, International, Federal, State, Provincial and local laws and regulations. Spills are very slippery and should be cleaned up promptly. Unless released material is cleaned up immediately for reprocessing, recycling, or reuse, a release of 100 lbs (45.36 kgs) (approximately 257 gallons or 973 liters of product) may trigger the reporting requirements under the United States EPA's CERCLA Section 103.

**Personal Precautions:** Wear appropriate personal protective equipment when cleaning up a spill

**Environmental Precautions:** U.S.A. regulations may require reporting spills of this material that could reach any surface waters. Report spills to all applicable National, International, Federal, State, Provincial and local authorities and/or the United States National Response Center at (800) 424-8802 as appropriate or required

## **7. Handling & Storage**

**Handling:** Avoid breathing vapors or mists. Avoid contact with eyes, skin, or clothing. Wash thoroughly after handling and before eating, smoking or using toilet facilities. Do not swallow product. Do not eat, drink or smoke in work areas.

**Storage:** Do not store near heat, spark, flame or strong oxidizers. Keep containers closed when not in use. Store in a well ventilated area. Properly bond and ground containers and transferring equipment when transferring this product to different containers. Store as a combustible liquid, Store in accordance with National Fire Protection Association recommendations or applicable National, Provincial and local laws and regulations.

**Container Warnings:** Container is not designed to contain pressure. Do not use pressure to empty container or it may rupture with explosive force. Empty containers retain product residue (solid, liquid and/or vapor) and can be dangerous. Do not cut, weld, braze, solder, drill, grind or expose containers to heat, flame, sparks, static electricity or other sources of ignition. There may explode and cause injury or death. Empty containers should be completely drained, properly closed and promptly returned to a drum reconditioner or disposed of properly

**Product Name: 137CTPW Carbon Treat Premium Winter**

**8. Exposure Controls and Personal Protection**

**Occupational Exposure Limits**

<b>Ingredient</b>	<b>OSHA TWA</b>	<b>OSHA STEL</b>	<b>ACGIH TWA</b>	<b>ACGIH STEL</b>
Heavy Aromatic (petroleum) solvent Naphtha	300 mg/m <sup>3</sup> 50 ppm		N/E	
Naphthalene	100 ppm 435 mg/m <sup>3</sup>		10 ppm	15 ppm
2-Ethylhexyl Nitrate	5 ppm, 8 & 12 hour TWA (supplier recommendation)	N/E	N/E	N/E
2-Butoxyethanol	50 ppm		25 ppm	75 ppm
1,2,4- Trimethylbenzene	125 mg/m <sup>3</sup> 25 ppm		125 mg/m <sup>3</sup> 25 ppm	
Light Aromatic (petroleum) solvent Naphtha	5 ppm, 12 hour TWA (supplier recommendation)			
Xylene	435 mg/m <sup>3</sup> 100 ppm		435 mg/m <sup>3</sup> 100 ppm	
Petroleum Distillate			200 mg/m <sup>3</sup>	
Ethylbenzene	435 mg/m <sup>3</sup> 100 ppm		100 ppm	125 ppm
Light Ends of Polyethylenebenzene Residue	N/E		N/E	
Vinyl Acetate	30mg/m <sup>3</sup> 10 ppm		35 mg/m <sup>3</sup> 10 ppm	

(s)-Skin exposure

(p) proposed limit

(c) – Ceiling limit

(l) Recommended exposure limit

(u) supplier limit

(N/E) – not established

**Product Name: 137CTPW Carbon Treat Premium Winter**

## **8. Exposure Controls and Personal Protection continued**

### **Other Exposure Limits**

**Engineering Controls:** Good general ventilation should be used. If applicable use process enclosures, local exhaust ventilation and other engineering controls to maintain airborne levels below recommended exposure limits.

### **Personal Protective Equipment**

**Gloves:** Impervious oil resistant gloves such as Neoprene, Nitrile rubber

**Protective Clothing:** Apron and long sleeves recommended

**Eye Protection:** Chemical goggles or safety goggles

**Respiratory Protection:** None required under conditions of normal use. Use approved full face respirator with an organic cartridge if the recommended exposure limit is exceeded or when working with this material in a confined space. Use self-contained breathing apparatus for entry into confined spaces, for poorly ventilated areas and for cleaning up large spill cleanup sites.

## **9. Physical and Chemical Properties**

**Flash Point:** 122°F (50°C) PMCC ASTM D-93

**Specific Gravity:** 0.9043

**Upper Flammable Limit (UEL):** Not determined

**Lower Flammable Limit (LEL):** Not determined

**Vapor Pressure:** <0.1 mm Hg @ 20°C (68°F)

**Vapor Density (air = 1) :** >1

**Percent Volatile:** >80%

**Evaporation Rate:** <1 (Butyl Acetate = 1)

**pH:** Not applicable

**Boiling Point:** Decomposes above 100°C (212°F)

**Melting Point:** Not applicable

**Appearance:** Tan to dark color

**Odor:** Aromatic solvent odor

**Solubility in Water:** Negligible

***The above data are typical values and do not constitute a specification. Vapor pressure data are calculated unless otherwise specified***

**Product Name: 137CTPW Carbon Treat Premium Winter**

**10. Stability and Reactivity**

**Stability:** Stable at normal temperatures and storage conditions

**Materials to Avoid:** Strong Oxidizers

**Polymerization:** Not expected to occur under conditions of normal use

**Thermal Decomposition:** 2-Ethylhexyl Nitrate in this product decomposes above 100°C (212°F). Oxides of carbon and nitrogen and by-products of incomplete combustion may form.

**Conditions to Avoid:** Products containing 2-Ethylhexyl Nitrate or solvents should not be exposed to steam, sparks, flames or hot surfaces. Rapid gas evolution during decomposition may lead to bursting of containers and may be explosive if heated under confinement.

**11. Toxicological Information:**

**Routes of Exposure:** Skin, eyes, ingestion and inhalation

**Target Organs:** Skin, eyes, upper respiratory tract, liver, spleen, kidneys

**Acute Exposure**

**Ingestion:** Harmful if swallowed. Nausea, abdominal discomfort, diarrhea

**Eye Contact:** Liquid contact produces severe irritation to the eyes

**Skin Contact:** Prolonged and repeated skin contact may cause redness, severe irritation and defatting of skin. Product may be absorbed through skin.

**Inhalation:** Inhalation of vapors can cause headache, dizziness, nausea, or decreased blood pressure.

**Dermal Sensitization:** This product is not expected to be a dermal sensitizer

**Inhalation Sensitization:** Product is not considered to be an inhalation sensitizer

**Carcinogenicity:**

This product contains 0.4 – 0.9% of Naphthalene CAS #91-20-3, 2-5% Ethylbenzene CAS #100-41-4 and 0.02-0.3% Vinyl Acetate CAS #108-05-4 which are chemicals found on the National Toxicology Programs Annual Reports, International Agency for Cancer Research's Monographs or OSHA's Subpart Z list as suspected human cancer causing agents.

This product contains 0.4 to 0.9% of Naphthalene CAS #91-20-3, 2-5% Ethylbenzene CAS #100-41-4 and 0.02-0.3% Vinyl Acetate CAS #108-05-4 which are chemicals known to the State of California to cause cancer and/or birth defects.

2-Butoxyethanol has been found to show teratogenic effects in laboratory animals

**Product Name: 137CTPW Carbon Treat Premium Winter**

**11. Toxicological Information continued:**

**Additional Toxicological Information:**

**Acute toxicity**

**2-Ethylhexyl Nitrate**

**Acute Inhalation Toxicity:** LC50 1 hour >639 ppm (rats)

**Acute Oral Toxicity LD50:** >9,640 mg/kg (rats)

**Acute Dermal Toxicity: LD50:** >4,820 mg/kg (rabbits)

**Heavy Aromatic Naphtha:**

**Acute Inhalation Toxicity:** LC50 6 hour >11.7 mg/l (rats)

**Acute Oral Toxicity LD50:** >5,000 mg/kg (rats)

**Acute Dermal Toxicity: LD50:** >3,160 mg/kg (rabbits)

**Light Aromatic Naphtha**

**Acute Inhalation Toxicity:** LC50 6 hour >14.4 mg/l (rats)

**Acute Oral Toxicity LD50:** >5,000 mg/kg (rats)

**Naphthalene:**

**Acute Inhalation Toxicity:** LC50 15 minutes >0.34 mg/l (rats)

**Acute Oral Toxicity LD50:** 1,780 mg/kg (rats)

**Acute Dermal Toxicity: LD50:** 10,000 mg/kg (rabbits)

**2-Butoxyethanol**

**Acute Inhalation Toxicity:** LC50 4 hours > 450 ppm (rats)

**Acute Oral Toxicity LD50:** 470 mg/kg (rats)

**Acute Dermal Toxicity: LD50:** 220 mg/kg (rabbits)

**Naphthalene**

**Acute Inhalation Toxicity:** LC50 8 hours > 100 ppm (rats)

**Acute Oral Toxicity LD50:** 2,000 mg/kg (rats)

**Acute Dermal Toxicity: LD50:** 2,500 mg/kg (rats)

**Product Name: 137CTPW Carbon Treat Premium Winter**

**11. Toxicological Information continued:**

**Additional Toxicological Information:**

**1,2,4 -Trimethylbenzene**

**Acute Oral Toxicity LD50:** 5 g/kg (rats)

**Vinyl Acetate**

**Acute Inhalation Toxicity:**

**Acute Oral Toxicity LD50:** 2,900 mg/kg (rat)

**Acute Dermal Toxicity: LD50:** 2,335 mg/kg (rabbit)

**Xylene**

**Acute Inhalation Toxicity:** LC50 1hour > 340 mg/m<sup>3</sup> (rats)

**Acute Oral Toxicity LD50:** 490 mg/kg (rats)

**Acute Dermal Toxicity: LD50:** >2,000 mg/kg (rats)

**Petroleum Distillates:**

**Acute Inhalation Toxicity:** LC50 4hour > 1400 ppm (rats)

**Acute Oral Toxicity LD50:** 6 g/kg (rats)

**Acute Dermal Toxicity: LD50:** >2,000 mg/kg (rats)

**12. Environmental and Ecological Information**

**Ecotoxicity**

**2-Ethylhexyl Nitrate**

24 hour LC50: 145 mg/l Trout

48 hour LC50: 116 mg/l Trout

24 hour LC50: 6.5 mg/l Bluegill

48 hour LC50: 6.0 mg/l Bluegill

**Heavy Aromatic Naphtha**

96 hour LC50: 4.2-20.8 mg/l Fathead minnows

96 hour LC50: >50 mg/l Pimephales promelas

48 hour EC50: 0.95 mg/l Daphina Magna

**2-Butoxyethanol**

24 hour LC50: 1700 mg/l Carassius auratus

48 hour LC50: 1880 mg/l Leuciscus idus

96 hour LC50: 2950 mg/l Lepomis macrochirus

24 hour EC50: 1720 – 1850 Daphina Magna

**Product Name: 137CTPW Carbon Treat Premium Winter**

**12. Environmental and Ecological Information continued**

**Ecotoxicity**

**Light Aromatic Naphtha:**

48 hour LC50: 4.2 mg/l white crappie

**1,2,4-Trimethylbenzene:**

96 hour LC50: 7.72 mg/l Pimephales promelas

**Naphthalene:**

24 hour LC50: 7.76 mg/l Pimephales promelas

48 hour LC50: 6.35 mg/l Pimephales promelas

96 hour LC50: 6.08 mg/l Pimephales promelas

96 hour LC50: 0.5 mg/l Micropeterus salmodies

96 hour LC50: 18 mg/l Oncorhynchus mykiss

24 hour EC50: 10.64 mg/l Artemia salina

24 hour EC50: 17 mg/l Daphina Magna

48 hour EC50: 2.16 mg/l Daphina Magna

**Xylene:**

96 hour LC50: 3.3 mg/l Oncorhynchus mykiss

96 hour LC50: 14,400 mg/l Bluegill Machrochrus

**Vinyl Acetate:**

96 hour LC50: 18 mg/l Lepomis macrochirus

96 hour LC50: 14 mg/l Pimephales promelas

**Petroleum Distillate:**

24 hour LC50: 5.5 ml/l Dendronereides heteropoda

48 hour LC50: 5.9 ml/l Dendronereides heteropoda

96 hour LC50: 1.5 ml/l Dendronereides heteropoda

**Biodegradation:** This product is not readily biodegradable

**Bioaccumulation:** Product has the potential to bioaccumulate, however metabolism or physical properties may reduce the bioconcentration or limit bioavailability.

**Water Class Hazard (Germany):** WK-3 according to appendix 4 VwVwS dated 27.7.2005

Do not allow product to reach ground water, water course or sewage system

## Product Name: 137CTPW Carbon Treat Premium Winter

### **13. Disposal Considerations**

**Waste Handling and Disposal:** This product in its neat state when discarded or disposed of is a hazardous waste according to Federal Regulations 40CFR 261.4 (b)(4) due to its reactivity. Unless released material is cleaned up immediately for reprocessing, recycling, or reuse, a release of 100 lbs (45.36 kgs) (approximately 257 gallons or 973 liters of product) may trigger the reporting requirements under the United States EPA's CERCLA Section 103. Dispose of product in accordance with all applicable National, Federal, State, Provincial and local laws and regulations. Do not re-use empty containers

### **14. Transport Information**

**US DOT Classification Non-Bulk:** UN 1993, Flammable Liquids, N.O.S. (Heavy Aromatic Naphtha, Light Aromatic Naphtha, Petroleum Distillates, 2-Ethylhexyl Nitrate, 2-Butoxyethanol), 3, PGIII

**US DOT Classification Bulk:** 275 and 330 gallon tote: UN 1993, Flammable Liquids, N.O.S. (Heavy Aromatic Naphtha, Light Aromatic Naphtha, Petroleum Distillates, 2-Ethylhexyl Nitrate, 2-Butoxyethanol), 3, PGIII, RQ, (Xylene), Marine Pollutant, (2-Ethylhexyl Nitrate, Naphthalene, Petroleum Naphtha, 1,2,4-Trimethylbenzene)  
>1,000 gallons: UN 1993, Flammable Liquids, N.O.S. (Heavy Aromatic Naphtha, Light Aromatic Naphtha, Petroleum Distillates, 2-Ethylhexyl Nitrate, 2-Butoxyethanol), 3, PGIII, RQ, (Xylene, Naphthalene, Ethylbenzene), Marine Pollutant, (2-Ethylhexyl Nitrate, Naphthalene, Petroleum Naphtha, 1,2,4-Trimethylbenzene)

**IMDG Classification:** 5 gallon pail, 55 gallon drums: UN 1993, Flammable Liquids, N.O.S. (Heavy Aromatic Naphtha, Light Aromatic Naphtha, Petroleum Distillates, 2-Ethylhexyl Nitrate, 2-Butoxyethanol), 3, PGIII, RQ, (Xylene), Marine Pollutant, (2-Ethylhexyl Nitrate, Naphthalene, Petroleum Naphtha, 1,2,4-Trimethylbenzene)

275 and 330 gallon tote: UN 1993, Flammable Liquids, N.O.S. (Heavy Aromatic Naphtha, Light Aromatic Naphtha, Petroleum Distillates, 2-Ethylhexyl Nitrate, 2-Butoxyethanol), 3, PGIII, RQ, (Xylene), Marine Pollutant, (2-Ethylhexyl Nitrate, Naphthalene, Petroleum Naphtha, 1,2,4-Trimethylbenzene)

**IATA/ICAO Classification:** UN 1993, Flammable Liquids, N.O.S. (Heavy Aromatic Naphtha, Light Aromatic Naphtha, Petroleum Distillates, 2-Ethylhexyl Nitrate, 2-Butoxyethanol), 3, PGIII

**Product Name: 137CTPW Carbon Treat Premium Winter**

**15. Regulatory Information**

**Hazard Symbols**

**EU**



**Xi irritant  
Xn Harmful**

**Relevant R Phrases:**

**R10 Flammable**

**R20 Harmful by inhalation**

**R22 Harmful if swallowed**

**R36/37/38 Irritating to eyes, respiratory system and skin**

**R36/38 Irritating to eyes and skin**

**R36 Irritating to eyes**

**R38 Irritating to skin**

**R40 Limited evidence of a carcinogenic effect**

**R50/53 Very toxic to aquatic organisms may cause long term adverse effects in the aquatic environment**

**R51/53 Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment**

**R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in aquatic environment**

**R65 Harmful: may cause lung damage if swallowed**

**S2 Keep out of the reach of children**

**S23 Do not breathe gas/fumes/vapour/spray**

**S24 Avoid contact with skin**

**S25 Avoid contact with eyes**

**S26 in case of contact with eyes rinse immediately with plenty of water and seek medical advice**

**S36/37/39 Wear suitable protective clothing, gloves and eye/face protection**

**S62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label**

Product Name: 137CTPW Carbon Treat Premium Winter

**15. Regulatory Information continued**

**Relevant hazard phrases**

- H226 – Flammable liquid or vapor
- H302 – Harmful if swallowed
- H304- May be fatal if swallowed and enters airways
- H312 – Harmful in contact with skin
- H315 – Causes skin irritation
- H319 – Causes serious eye irritation
- H332 – Harmful if inhaled
- H335 – May cause respiratory irritation
- H351 – Suspected of causing cancer
- H-400 – Very toxic to aquatic life
- H-410 – Very toxic to aquatic life with long lasting effects
- H411 – Toxic to aquatic life with long lasting effects

**GHS**



**US Regulations**

**TSCA Inventory:** All of the components in this material are on the US TSCA Inventory or are exempt.

**State of California Proposition 65:** This product contains 0.4-0.9% of Naphthalene CAS #91-20-3, 2-5% Ethylbenzene CAS #100-41-4 and 0.02-0.3% Vinyl Acetate CAS #108-05-4 which are chemicals known to the State of California to cause cancer and/or birth defects.

2-Butoxyethanol has been found to show teatogenic effects in laboratory animals

**Product Name: 137CTPW Carbon Treat Premium Winter**

**15. Regulatory Information continued**

**US EPA SARA Title III and CERCLA Listings and Reportable Quantities**

**US EPA Section 311/313 Classifications**

Acute	Chronic	Fire	Pressure	Reactivity
X	X			X

**US EPA Section 313 Chemicals**

**I. Section 302/304 Extremely Hazardous**

Component	CAS#	%	RQ (lbs.)	RQ (gal*)
Vinyl Acetate	108-05-4	0.02-0.3	5,000	280,324

**II. CERCLA Section 102(a) & 302.4 Hazardous Substance & Section 313 Toxic Chemical**

Component	CAS#	%	RQ (lbs.)	RQ (gals.)
Naphthalene	91-20-3	0.4-0.9	100	1,437
Xylene	1330-20-7	4-7	100	190
Vinyl Acetate	108-05-4	0.02-0.3	5,000	280,324
Ethylbenzene	100-41-4	2-5	1000	2,632

**Section 313 Chemicals**

Component	CAS#	%
2-Butoxyethanol	111-76-2	1-5
Naphthalene	91-20-3	0.4 -0.9
Xylene	1330-20-7	4-7
Vinyl Acetate	108-05-4	0.02 – 0.3
Ethylbenzene	100-41-4	2-5

\*Product RQ for Stationary Source to release Regulatory Requirement RQ as specified by CERCLA.

**Product Name: 137CTPW Carbon Treat Premium Winter**

**15. Regulatory Information continued**

**US Tariff Heading Number:** 3811.90.0000

**Schedule B Number:** 3811.90.0000

**Other Regulations:**

**Canada:** All of the ingredients of this product are in compliance with the Canadian Environmental Protection Act and are present on the Domestic Substance List

**Canadian WHMIS Classifications and Symbols:**

This product is a WHMIS controlled product. This product is a Class B Combustible and a class D2 material



**EEC:** All components are in compliance with the EC Seventh Amendment Directive 92/32/EEC

**16. Other Information**

**For additional information call +1 314-865-4100 (outside the US and Canada) or 1-800-325-9962 inside the United States and Canada.**

Although the information and recommendations set forth herein (hereafter referred to as information) are presented in good faith and believed to be accurate and factual as of the date hereof, Schaeffer Mfg. Company makes no representation as to the completeness or accuracy thereof. Information is supplied upon the condition that the person receiving the same will make their own determination as to its safety and suitability for their purposes prior to use. In no event will Schaeffer Mfg. Company be responsible for damages of any natures whatsoever resulting from the use or reliance upon information. **No representation or warranty, either expressed or implied, of merchantability or fitness for a particular purpose is made with respect to information of the product to which the information refers. Compliance with all applicable federal, state, and local regulations remains the responsibility of the user.**