

# MATERIAL SAFETY DATA SHEET

<b>Manufacturer:</b> Schaeffer Mfg. Company		<b>Emergency Response Number:</b>				
<b>Address:</b> 102 Barton Street		314-865-4105 or				
<b>Address:</b> St. Louis, MO 63104		800-325-9962				
<b>SECTION 1 – PRODUCT INFORMATION</b>						
<b>Chemical Family:</b> Petroleum Hydrocarbons and Additives		<b>Trade Name:</b> #200S Silver Streak® Special Multi Lube Super Ultra Light				
<b>Formula:</b> Proprietary Mixture						
<b>SECTION 2 – HAZARDOUS INGREDIENTS</b>						
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES	CAS Number	%	Exposure Limits			
			TVL		PEL	
			ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Mixture of Petroleum Oils	64742-16-1, 64741-56-6, 64742-53-6, 64742-01-4, 64742-57-5, 64742-62-7	62-64		5		5
Polyalphaolefin Synthetic Base Fluid	68037-01-4	15-20		5		5
Acetylene Black	1333-86-4	3-7		3.5		3.5
Graphite	7782-42-5	3-7		2		15 MPCCF
Aluminum Paste	7429-90-5	1-3		10		15
Molybdenum Disulfide	1317-33-5	3-7		10		15
Olefin Copolymer Tackiness Additive	3-4			NE		NE
Organophilic Clay	71011-25-1, 68953-58-2	1-2		NE		NE
<b>Section 3 – PHYSICAL DATA</b>						
<b>Boiling Point:</b>	600°F/315.5°C	<b>Specific Gravity:</b>	1.003			
<b>Vapor Pressure (mm, Hg):</b>	Not Determined	<b>% Volatile:</b>	Nil			
<b>Vapor Density (Air = 1):</b>	Not Determined	<b>Evaporation Rate: (=1)</b>	Not Established			
<b>Solubility in Water:</b>	Insoluble	<b>pH:</b>	Not Applicable			
<b>Appearance and Odor:</b> Silver, black color, tacky petroleum odor.						
<b>SECTION 4 - FIRE AND EXPLOSION HAZARD DATA</b>						
<b>Flash Point (Method) °F° C:</b> 420°-425°F/215.56°-218.33°C C.O.C. (ASTM D-92)		<b>Flammability Limits UEL &amp; LEL ----</b> Not Determined				
<b>Extinguishing Media:</b> Carbon dioxide foam, dry chemical foam, sand, earth, waterfog.						
<b>Special Fire Fighting Procedures:</b> For fires involving this material, do not enter any enclosed or confined space without protective equipment including self-contained breathing apparatus.						
<b>Unusual Fire &amp; Explosion Hazards:</b> Dense Black Smoke.						
<b>SECTION 5 - REACTIVITY HAZARD DATA</b>						
<b>STABILITY</b>	<input checked="" type="checkbox"/> STABLE	<input type="checkbox"/> UNSTABLE	<b>Hazardous Decomposition</b> <input type="checkbox"/> WILL <input checked="" type="checkbox"/> WILL NOT OCCUR			
<b>Conditions to Avoid:</b> None						
<b>Incompatibility (Mat. to avoid):</b> Strong oxidizers and reducers						
<b>Hazardous Decomposition Products:</b> Oxides of carbon, sulfur and by products of incomplete combustion.						
<b>Conditions to Avoid:</b> None						
<b>SECTION 6 - HEALTH HAZARD DATA</b>						
<b>Threshold Limit Value and Sources:</b> 5.0/mg/m <sup>3</sup> for oil mist. OSHA & ACGIH.						
<b>Acute Effects of Overexposure:</b>						
<b>Ingestion:</b>	Nausea and Diarrhea. Tackiness agents in this product may be possibly coagulated by stomach acids.					
<b>Eye Contact:</b>	Irritation and redness to eyes					
<b>Skin Contact:</b>	Prolonged and repeated contact with the skin can cause irritation and redness to skin.					
<b>Inhalation:</b>	Vapors can be given off under high heat conditions excessive breathing of vapors can cause irritation of the respiratory tract.					
<b>CHRONIC EFFECTS OF OVEREXPOSURE:</b> None currently known						
<b>Emergency and First Aid Procedures:</b>						
<b>Swallowing:</b>	If conscious give 2 glasses of water to drink. Do not induce vomiting. Seek medical attention immediately.					
<b>Skin:</b>	Wash skin thoroughly with soap and water. Launder contaminated clothing.					
<b>Inhalation:</b>	Remove victim to fresh air. If breathing is labored administer oxygen. If breathing has stopped start artificial respiration immediately.					
<b>Eyes:</b>	Flush eyes with clear, cool, clean water for 15 minutes. Seek medical attention immediately					
<b>SECTION 7 – SPILL OR LEAK PROCEDURES</b>						
<b>Environmental Impact:</b> This material is not expected to present any environmental problems other than those associated with oil spills. If spilled into a watercourse, call the Coast Guard Toll Free No. 800-424-8802.						
<b>Procedures To Be Taken If Material Is Released or Spilled:</b> Immediately absorb spilled material with absorbent clay or other suitable material. Keep out of sewers and waterways. Shovel up and place in a hazardous waste disposal drum.						
<b>Waste Disposal Method:</b> Dispose of at an approved waste or disposal site facility in accordance with all applicable federal, state and local laws and regulations. This product is not considered to be an RCRA hazardous waste.						

Date Prepared: 4/30/04

OF-1049 Rev. (1999)

<b>SECTION 8 – SPECIAL PROTECTION INFORMATION</b>	
<b>Respiratory Protection:</b>	None required under ordinary conditions of use.
<b>Ventilation:</b>	No special requirement under ordinary conditions of use and with adequate ventilation.
<b>Eye Protection:</b>	Goggles or face shield.
<b>Protective Clothing:</b>	Neoprene or oil resistant gloves.
<b>SECTION 9 – SPECIAL PRECAUTIONS</b>	
<b>Precautions To Be Taken In Handling and Storage:</b> Do not store near heat, spark, flame or strong oxidizers. Keep containers closed when not in use.	
<b>Special Comments:</b> Remove greasel soaked clothing, launder before reuse. Wash skin thoroughly with soap and water after handling and before eating, smoking, or using toilet facilities. Keep away from food and feed products	
<b>SECTION 10 – ADDITIONAL HEALTH AND TOXICOLOGICAL DATA</b>	
<b>HMIS &amp; NFPA Ratings:    Health = 1            Fire = 1            Reactivity = 0</b>	
This product does not contain any of the chemicals listed on the National Toxicology Program Annual Reports on Carcinogens, The International Agency for Cancer Research Monographs and OSHA's 1910.10 Subpart Z List.	
This product does not contain any chemicals that are found on the State of California's Proposition 65 List for chemicals classified as potential reproductive or cancer causing agent.	
SARA Title III Information: This product contains 1-3% Aluminum Paste CAS#7429-90-5	
All of the components in this material are on the US TSCA Inventory List. All of the components of this material are in compliance with the Canadian Environmental Protection Act, the EC Seventh Amendment Directive 921321EEC and the chemical notification requirements of Australia, Austria and the Environmentally Hazardous Ordinance of Switzerland.	

Although the information and recommendations set forth herein (hereafter referred to as information) are presented in good faith and believed to be accurate and factual as of the date hereof, Schaeffer Mfg. Company makes no representation as to the completeness or accuracy thereof. Information is supplied upon the condition that the person receiving the same will make their own determination as to its safety and suitability for their purposes prior to use. In no event will Schaeffer Mfg. Company be responsible for damages of any natures whatsoever resulting from the use or reliance upon information. **No representation or warranty, either expressed or implied, of merchantability or fitness for a particular purpose is made with respect to information of the product to which the information refers.**