

# MATERIAL SAFETY DATA SHEET

<b>Manufacturer:</b> Schaeffer Mfg. Company		<b>Emergency Response Number:</b> 314-865-4105 (24-hour emergency number) or 800-325-9962				
<b>Address:</b> 102 Barton Street						
<b>Address:</b> St. Louis, MO 63104						
SECTION 1 – PRODUCT INFORMATION						
<b>Chemical Family:</b> Petroleum Hydrocarbons and Additives		<b>Trade Name:</b> #200 Silver Streak® Multi Lube Spray				
<b>Formula:</b> Proprietary Mixture						
SECTION 2 – HAZARDOUS INGREDIENTS						
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES	CAS Number	%	Exposure Limits			
			TVL		PEL	
			ppm	mg/m <sup>3</sup>	ppm	Mg/m <sup>3</sup>
Medium Aliphatic Solvent Naphtha	64742-88-7	9-11	100		100	
Acetone	67-64-1	9-11	750		1000	2400
Petroleum Base Oil	64742-16-1	72-74		5		5
Molybdenum Disulfide	1317-33-5	4-6		10		15
Aluminum Paste	7429-90-5	1		NE		NE
Section 3 – PHYSICAL DATA						
<b>Boiling Point:</b>	>300 F/148.89 C	<b>Specific Gravity:</b>	.9321			
<b>Vapor Pressure (mm, Hg):</b>	Not Determined	<b>% Volatile:</b>	20%			
<b>Vapor Density (Air = 1):</b>	Not Determined	<b>Evaporation Rate: (=1)</b>	Not Determined			
<b>Solubility in Water:</b>	Insoluble	<b>pH:</b>	Not Applicable			
<b>Appearance and Odor:</b> Black color, tacky, solvent odor.						
SECTION 4 - FIRE AND EXPLOSION HAZARD DATA						
<b>Flash Point (Method) (A)F/(A)C:</b> 75 -110 F/23.89 -43.33 C PMCC		<b>Flammability Limits UEL &amp; LEL</b> ----10 / 1.57				
<b>Extinguishing Media:</b> Carbon dioxide foam, dry chemical foam.						
<b>Special Fire Fighting Procedures:</b> For fires involving this material, do not enter any enclosed or confined space without protective equipment including self-contained breathing apparatus.						
<b>Unusual Fire &amp; Explosion Hazards:</b> This product is packaged in spray cans and as such, the container may explode.						
SECTION 5 - REACTIVITY HAZARD DATA						
<b>STABILITY</b>	<input checked="" type="checkbox"/> STABLE	<input type="checkbox"/> UNSTABLE	<b>Hazardous Decomposition</b> <input type="checkbox"/> WILL <input checked="" type="checkbox"/> WILL NOT OCCUR			
<b>Conditions to Avoid:</b> High heat, high energy ignition sources, open flame						
<b>Incompatibility (Mat. to avoid):</b> Strong oxidizers and reducers						
<b>Hazardous Decomposition Products:</b> Oxides of carbon and ketones						
<b>Conditions to Avoid:</b> None						
SECTION 6 - HEALTH HAZARD DATA						
<b>Threshold Limit Value and Sources:</b> 5.0/mg/m <sup>3</sup> for oil mist. OSHA & ACGIH.						
<b>Acute Effects of Overexposure:</b>						
<b>Ingestion:</b>	Ingestion of this product may be harmful or fatal.					
<b>Eye Contact:</b>	Severe irritation and redness to eyes. Vision may become blurred.					
<b>Skin Contact:</b>	Prolonged and repeated contact with the skin can cause irritation and redness to skin.					
<b>Inhalation:</b>	Inhalation of large amounts of vapor may cause nausea, chills, headache, light headedness, drowsiness and irritation of the respiratory tract and unconsciousness					
<b>CHRONIC EFFECTS OF OVEREXPOSURE:</b> None currently known						
<b>Emergency and First Aid Procedures:</b>						
<b>Swallowing:</b>	If swallowed, have victim drink several glasses of water. Do not induce vomiting. If vomiting occurs, give fluids again. Do not give anything to an unconscious or convulsing person. Seek medical attention immediately.					
<b>Skin:</b>	Wash skin thoroughly with soap and water. Launder contaminated clothing.					
<b>Inhalation:</b>	Remove victim to fresh air. If breathing has stopped start artificial respiration immediately.					
<b>Eyes:</b>	Flush eyes with clear, cool, clean water for 15 minutes. Hold the eyelids apart during flushing to ensure rinsing of the entire surface of the eyes and lids with water. Seek medical attention immediately					
SECTION 7 – SPILL OR LEAK PROCEDURES						
<b>Environmental Impact:</b> This material is not expected to present any environmental problems other than those associated with oil spills. If spilled into a watercourse, call the Coast Guard Toll Free No. 800-424-8802.						
<b>Procedures To Be Taken If Material Is Released or Spilled:</b> Immediately absorb spilled material. Remove sources of combustion or extreme heat. Absorb with absorbent clay, diatomaceous earth or other suitable material. Place in an approved hazardous waste container. Keep out of sewers and waterways.						
<b>Waste Disposal Method:</b> Dispose of at an approved waste or disposal site facility in accordance with all applicable federal, state and local laws and regulations. This product is considered to be an RCRA hazardous waste if it becomes a waste material. It would be an ignitable hazardous waste D001.						
SECTION 8 – SPECIAL PROTECTION INFORMATION						
<b>Respiratory Protection:</b>	None required under ordinary conditions of use.					
<b>Ventilation:</b>	No special requirement under ordinary conditions of use and with adequate ventilation.					
<b>Eye Protection:</b>	Goggles of face shield.					
<b>Protective Clothing:</b>	Solvent resistant gloves.					

Date Prepared: 01/02/2008

OF-1049 Rev. (1999)

SECTION 9 – SPECIAL PRECAUTIONS		
<b>Precautions To Be Taken In Handling and Storage:</b> Do not store near high heat or strong oxidizers. Keep containers closed when not in use. Avoid contact with skin.		
<b>Special Comments:</b> Remove oil soaked clothing, launder before reuse. Wash skin thoroughly with soap and water after handling. Keep away from food and feed products		
SECTION 10 – ADDITIONAL HEALTH AND TOXICOLOGICAL DATA		
<b>HMIS &amp; NFPA Ratings:    Health = 3            Fire = 3            Reactivity = 0</b>		
Under no circumstances should vomiting be induced. Vomiting can cause aspiration of product into lungs.		
This product does not contain any of the chemicals listed on the National Toxicology Program Annual Reports on Carcinogens, The International Agency for Cancer Research Monographs and OSHA's 1910.10 Subpart Z List.		
This product does not contain any chemicals that are found on the State of California's Proposition 65 List for chemicals classified as potential reproductive or cancer causing agent.		
SARA Title III Information: This product contains 9-11% Acetone CAS#67-64-1		
All components are on the US TSCA Inventory List and are in compliance with the Canadian Environmental Protection Act.		
DOT Information: 12-160z cans per case: ORM-D IMDG Maritime: UN1950, Aerosols, (Medium aliphatic solvent naphtha, acetone), 2.1, Limited Quantity		

Although the information and recommendations set forth herein (hereafter referred to as information) are presented in good faith and believed to be accurate and factual as of the date hereof, Schaeffer Mfg. Company makes no representation as to the completeness or accuracy thereof. Information is supplied upon the condition that the person receiving the same will make their own determination as to its safety and suitability for their purposes prior to use. In no event will Schaeffer Mfg. Company be responsible for damages of any natures whatsoever resulting from the use or reliance upon information. **No representation or warranty, either expressed or implied, of merchantability or fitness for a particular purpose is made with respect to information of the product to which the information refers.**