

# MATERIAL SAFETY DATA SHEET

<b>Manufacturer:</b> Schaeffer Mfg. Company		<b>Emergency Response Number:</b>				
<b>Address:</b> 102 Barton Street		314-865-4105 or				
<b>Address:</b> St. Louis, MO 63104		800-325-9962				
<b>SECTION 1 – PRODUCT INFORMATION</b>						
<b>Chemical Family:</b> Petroleum Hydrocarbons and Additives		<b>Trade Name:</b> #221 Moly Ultra 800 E.P. #00				
<b>Formula:</b> Solvent refined paraffin base oils, aluminum complex thickener, extreme pressure additives, rust and oxidation inhibitors, molybdenum disulfide, tackiness agents.						
<b>SECTION 2 – HAZARDOUS INGREDIENTS</b>						
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES	CAS Number	%	Exposure Limits			
			TVL		PEL	
			ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
100% Pure Paraffin Base Oils	64742-01-4, 64742-57-0, 64742-62-7, 64742-54-7, 64742-65-0	80-90		5		5
Aluminum Benzoate Stearate (aluminum complex)		4-6		NE		NE
Antimony Dithiocarbamate	15890-25-2	1-2		0.5		0.5
Molybdenum Disulfide	1317-33-5	3-5		10		15
<b>Section 3 – PHYSICAL DATA</b>						
<b>Boiling Point:</b>	>600°F/315.5°C	<b>Specific Gravity:</b>	1.02			
<b>Vapor Pressure (mm, Hg):</b>	<.1	<b>% Volatile:</b>	Not Determined			
<b>Vapor Density (Air = 1):</b>	Not Determined	<b>Evaporation Rate: (=1)</b>	Not Applicable			
<b>Solubility in Water:</b>	Negligible	<b>pH:</b>	Not Applicable			
<b>Appearance and Odor:</b> Black color, tacky, slight smell						
<b>SECTION 4 - FIRE AND EXPLOSION HAZARD DATA</b>						
<b>Flash Point (Method) ° F° C:</b> 500°F/260°C C.O.C. (ASTM D-92)		<b>Flammability Limits UEL &amp; LEL</b> ----Not Determined				
<b>Extinguishing Media:</b> Carbon dioxide foam, dry chemical foam, sand, earth, waterfog.						
<b>Special Fire Fighting Procedures:</b> For fires involving this material, do not enter any enclosed or confined space without protective equipment including self-contained breathing apparatus.						
<b>Unusual Fire &amp; Explosion Hazards:</b> None expected.						
<b>SECTION 5 - REACTIVITY HAZARD DATA</b>						
<b>STABILITY</b> <input checked="" type="checkbox"/> STABLE <input type="checkbox"/> UNSTABLE		<b>Hazardous Decomposition</b> <input type="checkbox"/> WILL <input checked="" type="checkbox"/> WILL NOT OCCUR				
<b>Conditions to Avoid:</b> High heat, high energy ignition sources						
<b>Incompatibility (Mat. to avoid):</b> Strong oxidizers.						
<b>Hazardous Decomposition Products:</b> Oxides of carbon, sulfur, antimony, and nitrogen						
<b>Conditions to Avoid:</b> None						
<b>SECTION 6 - HEALTH HAZARD DATA</b>						
<b>Threshold Limit Value and Sources:</b> 5.0/mg/m <sup>3</sup> for oil mist. OSHA & ACGIH.						
<b>Acute Effects of Overexposure:</b>						
<b>Ingestion:</b>	Nausea and Diarrhea. Tackiness agents in this product may be possibly coagulated by stomach acids.					
<b>Eye Contact:</b>	Irritation and redness to eyes					
<b>Skin Contact:</b>	Prolonged and repeated contact with the skin can cause mild skin irritation.					
<b>Inhalation:</b>	Vapors can be given off under high heat conditions excessive breathing of vapors can cause irritation of the respiratory tract.					
<b>CHRONIC EFFECTS OF OVEREXPOSURE:</b> If ingested in large amounts or repeatedly, damage to the cardiovascular system and respiratory tract can occur.						
<b>Emergency and First Aid Procedures:</b>						
<b>Swallowing:</b>	If a large amount of this material is swallowed give a large amount of water to drink. Do not induce vomiting. Seek medical attention immediately. Treat medically for possible abdominal blockage.					
<b>Skin:</b>	Wash skin thoroughly with soap and water. Launder contaminated clothing.					
<b>Inhalation:</b>	Remove victim to fresh air. If breathing is labored administer oxygen. If breathing has stopped start artificial respiration immediately.					
<b>Eyes:</b>	Flush eyes with clear, cool, clean water for 15 minutes. Seek medical attention immediately					
<b>SECTION 7 – SPILL OR LEAK PROCEDURES</b>						
<b>Environmental Impact:</b> This material is not expected to present any environmental problems other than those associated with oil spills. If spilled into a watercourse, call the Coast Guard Toll Free No. 800-424-8802.						
<b>Procedures To Be Taken if Material Is Released or Spilled:</b> Immediately absorb spilled material with absorbent clay, diatomaceous earth or other suitable material. Keep out of sewers and waterways.						
<b>Waste Disposal Method:</b> Dispose of at an approved waste or disposal site facility in accordance with all applicable federal, state and local laws and regulations.						
<b>SECTION 8 – SPECIAL PROTECTION INFORMATION</b>						
<b>Respiratory Protection:</b>	None required under ordinary conditions of use.					
<b>Ventilation:</b>	No special requirement under ordinary conditions of use and with adequate ventilation.					
<b>Eye Protection:</b>	Goggles of face shield.					
<b>Protective Clothing:</b>	None required.					

Date Prepared: 4/30/04

OF-1049 Rev. (1999)

SECTION 9 – SPECIAL PRECAUTIONS		
<b>Precautions To Be Taken In Handling and Storage:</b> Do not store near high heat or strong oxidizers. Keep containers closed when not in use.		
<b>Special Comments:</b> Remove oil soaked clothing, launder before reuse. Wash skin thoroughly with soap and water after handling. Keep away from food and feed products		
SECTION 10 – ADDITIONAL HEALTH AND TOXICOLOGICAL DATA		
<b>HMIS &amp; NFPA Ratings: Health = 1      Fire = 1      Reactivity = 0</b>		
This product does not contain any of the chemicals listed on the National Toxicology Program Annual Reports on Carcinogens, The International Agency for Cancer Research Monographs and OSHA's 1910.10 Subpart Z List.		
This product does not contain any chemicals that are found on the State of California's Proposition 65 List for chemicals classified as potential reproductive or cancer causing agent.		
All of the components in this material are on the US TSCA Inventory. All components are in compliance with the Canadian Environmental Act.		

SARA Title III Information

Title III Section 302/304	Extremely Hazardous				
Component	CAS#	%	RQ (lbs.)	TPQ (lbs)	RQ*
None					
CERCLA Section 102 (a) Hazardous Substances					
Component	CAS#	%	RQ (lbs.)		RQ*
Antimony Dialkyldithiocarbamate	15890-25-2	1-2	5000		52,782.8
Section 313 Chemicals					
Component	CAS#	%			
Antimony Dialkyldithiocarbamate	15890-25-2	1-2			

\*Product RQ for Stationary Sources in case of a spill needed to release the component RQ

Although the information and recommendations set forth herein (hereafter referred to as information) are presented in good faith and believed to be accurate and factual as of the date hereof, Schaeffer Mfg. Company makes no representation as to the completeness or accuracy thereof. Information is supplied upon the condition that the person receiving the same will make their own determination as to its safety and suitability for their purposes prior to use. In no event will Schaeffer Mfg. Company be responsible for damages of any nature whatsoever resulting from the use or reliance upon information. **No representation or warranty, either expressed or implied, of merchantability or fitness for a particular purpose is made with respect to information of the product to which the information refers.**