

#228PGL SUPER HV PIVOT GEAR LUBE

Super HV Pivot Gear Lube is an extreme pressure, thixotropic semi-fluid grease that is specially formulated for use in the lubrication of gear boxes of center pivot irrigation systems.

Super HV Pivot Gear Lube is compounded from a blend of the finest select high viscosity index solvent refined, severely hydrofinished 100% paraffin base oils available. Blended into these 100% paraffin base oils fluids are an aluminum complex base thickener, carefully selected extreme pressure, anti-wear, lubricity agents, rust and oxidation and corrosion inhibitor additives and unique polymer base additive system. This formulation provides Super HV Pivot Gear Lubricant with the following performance features:

- Excellent flow-ability around bearings and gears even at low temperatures
- Thixotropic properties to thin down when worked by the motion of the gears and bearings and to thicken back to its original consistency after the gearbox is no longer in motion. This allows the Super HV Pivot Gear Lube the ability to provide flow back and heat transfer, while still remaining thicker in consistency in the outer areas of the gearbox in order to provide sealing to keep Super HV Pivot Gear Lube in and moisture and water contamination out.
- Excellent resistance to water washout and water spray off
- Excellent resistance to lubricant breakdown due to moisture contamination
- Excellent shear and mechanical stability
- High base oil viscosity (ISO 460) that provides Elastohydrodynamic (EHL) viscometrics and film forming characteristics for excellent resistance against wear for heavily loaded components.
- Superior anti-wear and extreme pressure protection and performance especially under heavily loaded and high shock loading conditions
- Excellent lubricity to prevent wear
- Excellent reversibility. This property allows Super HV Pivot Gear Lube to retain its' grease like consistency and remain around the bearings and gears during periods of heat, high shock loading, extreme pressure and severe mechanical action
- Excellent rust and oxidation inhibiting characteristics.
- Excellent protection against rust and corrosion
- Excellent resistance to oxidation and thermal degradation
- Excellent adhesive/cohesive properties in order to provide the Super HV Pivot Gear Lube with the ability to seal moisture out along with resisting washout, pound out, splatter or squeeze out during periods of high loads, vibration, shock loading, extreme pressure and severe mechanical action
- The ability to cling to and stay on metal surfaces. This property allows the Super HV Pivot Gear Lube with the ability to be carried to all of the moving mechanisms of the pivot gear drive in order to prevent wear and be adequately lubricated during adverse service conditions.
- Non-corrosiveness to yellow metals such as copper, brass, bronze and their alloys
- Very good sealing properties to prevent leakage of the Super HV Pivot Gear Lube from the pivot gear drive.

Incorporated into this blend of 100% paraffin base fluids, aluminum complex thickener, selected additives and the polymer base additive system is synthesized moly and a proprietary solid lubricant. The synthesized moly and this proprietary solid lubricant acting in synergism with each other plates themselves to the metal surfaces of the bearings.

Continued on Next Page

Once plated to the metal surfaces of the bearings, the synthesized moly and the proprietary solid lubricant form a long lasting solid lubricant film that is capable of withstanding pressures up to 500,000 pounds per square inch, thus giving the metal surfaces of the bearings the protection they need during periods of high speed, high shock loads and extreme pressure.

This reduction in friction and the ability to act as a “backstop” lubricant results in reduced wear and a reduction in contact area temperature. This in turn leads to increased pivot gearbox life, less downtime and extended lubrication cycles.

TYPICAL PROPERTIES

NLGI Grade

Worked Penetration 60 Strokes @ 77°F/25°C ASTM D-217

Type Thickener

Dropping Point °F/°C ASTM D-2265

Oxidation Stability ASTM D-942

PSI Loss @ 100 hours

Timken EP Test ASTM D-2509

Failure Load, lbs-f

Four Ball EP Test ASTM D-2596

Weld Point. Kgs

Four Ball Wear Test ASTM D-2266

Scar diameter, mm

Water Washout Test ASTM D-2164

% Weight Loss 175°F/79°C

Copper Strip Corrosion Test ASTM D-4048

Rust Inhibition Test ASTM D-1743

Rating

Emcor Rust Test ASTM D-6138

Distilled Water

Synthetic Sea Water

Base Oil Properties

Viscosity cSt @ 40°C ASTM D-445

Viscosity Index ASTM D-2270

Flash Point °F/°C ASTM D-92

00

425-450

Aluminum Complex

500°/260°

1.5

75

400

0.4

2.5%

1a

1,1,1

Pass

Pass

470-555

102

471°/244°