



TECHNICAL DATA

102 Barton Street, St. Louis, Missouri 63104

In-State (314) 865-4100/Out of State 800-325-9962/Fax (314) 865-4107 <http://www.schaefferoil.com>

#319 Moly Hi-Visc Boom Lube

Moly Hi-Visc Boom Lube is a high viscosity, adhesive lubricant used for forklifts, aerial lifts, telescoping booms and other sliding metal surfaces found in industrial and construction applications.

Moly Hi-Visc Boom Lube is an aerosol product that sprays easily as a thin, shear film and clings to vertical surfaces. Moly Hi-Visc Boom Lube contains Micron Moly®, a liquid soluble molybdenum which, once plated, forms a long lasting, slippery, tenacious lubricant film.

The Micron Moly® frictional modifier plus the high viscosity base oils prevent metal-to-metal contact and damaging frictional wear which results in:

- * **A Low Coefficient of Friction.**
- * **Increased Durability.**
- * **Long-lasting stay-in-place performance.**
- * **Reduced Maintenance**

TYPICAL PROPERTIES (of neat product)

| | |
|-------------------------------|-------------|
| API Gravity 60°F (ASTM D-287) | 29.2 |
| Specific Gravity | .88 |
| Flash Point °F/°C (ASTM D-92) | 475°/246° |
| Fire Point °F/°C (ASTM D-92) | 510°/265.5° |