



# **TECHNICAL DATA**

102 Barton Street, St. Louis, Missouri 63104

In-State (314) 865-4100/Out of State 800-325-9962/Fax (314) 865-4107 <http://www.schaefferoil.com>

---

## **#131TT TOP TIER GASOLINE FUEL ADDITIVE**

Top Tier Gasoline Fuel Additive is a concentrated multifunctional gasoline detergent additive that specially formulated for use in all types of gasoline to provide “Top Tier Performance Characteristics”

Top Tier Gasoline Fuel Additive when used at the recommended treatment ratio this unique provides the following premium performance benefits.

1. Clean up and keep clean performance to restore performance and maintain new performance.
2. Improved Carburetor Chamber Deposit control (CCD),
3. Improved Port Fuel Injector (PFI) deposit control and clean-up
4. Improved engine induction system deposit control and clean-up
5. Improved Intake Valve Deposit (IVD) deposit control and clean-up .
6. Modification of existing injector deposits, allowing for their removal and safe passage into the combustion chamber where they can be burned.
7. Superb piston deposit control to reduce the risk of engine seizure.
8. Increased engine performance.
9. Smoother idling.
10. Improved vehicle performance and responsiveness.
11. Improved drivability.
12. Excellent corrosion protection.
13. Better –than-New Fuel Economy. Not a restoration due to cleanliness.
14. Up to 2% improvement in fuel economy on new vehicles and up to 5% on older vehicles.
15. Fuel economy improvements with continued use.
16. Reduced emissions and particulates.
- 17.. Complete compatibility with engine and fuel system component materials.

Continued on Next Page

TD-131TT (12/118/05)

**TD-131TT**  
**Page 2**

Top Tier Gasoline Fuel Additive meets and exceeds the specified performance requirements of both the EPA and the California Air Resources Board (CARB).

**Treatment Ratio:**

**1 gallon of Top Tier Gasoline Fuel Additive to 4,000 gallons of Gasoline**

**Typical Properties**

Specific Gravity @ 60°F	0.868
Flash Point °F/°C, Pensky Martin ASTM D-93	100°/38°
Ash Content % wt. ASTM D-482	0%