

MATERIAL SAFETY DATA SHEET

Manufacturer: Schaeffer Mfg. Company		Emergency Response Number:				
Address: 102 Barton Street		314-865-4105 (24-Hour Emergency Number)				
Address: St. Louis, MO 63104		or 800-325-9962				
SECTION 1 – PRODUCT INFORMATION						
Chemical Family: None		Trade Name: #131C Soy Ultra Gasoline Additive Pint				
Formula: Proprietary Formulation						
SECTION 2 – HAZARDOUS INGREDIENTS						
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES	CAS Number	%	Exposure Limits			
			TVL		PEL	
			ppm	mg/m ³	ppm	mg/m ³
Xylene	1330-20-7	0-5.6	100	434	100	435
Ethylbenzene	100-41-4	6.83	100	435	100	435
Naphthalene	91-20-3	0.646	25		25	
Methyl Soyate	67762-38-2	Proprietary to formulation	NE		NE	
Proprietary Ingredients	Mixture – Trade Secret	23-25	NE		NE	
Petroleum Distillates	64742-47-8	60-70		200	NE	
Section 3 – PHYSICAL DATA						
Boiling Point:	IBP 298°F/148°C	Specific Gravity:	0.9191			
Vapor Pressure (mm, Hg):	Not Determined	% Volatile:	Not Determined			
Vapor Density (Air = 1):	>1	Evaporation Rate: (=1)	Not Determined			
Solubility in Water:	Insoluble	pH:	Not Applicable			
Appearance and Odor: Tan to dark color, aromatic and amine like odor						
SECTION 4 - FIRE AND EXPLOSION HAZARD DATA						
Flash Point (Method) °F/°C: 135°F/57°C PMCC (ASTM D-93)		Flammability Limits UEL & LEL ----Not Determined				
Extinguishing Media: CO ₂ , dry chemical foam, waterfog. Water or foam may cause frothing. Use water to cool exposed containers.						
Special Fire Fighting Procedures: Recommend wearing positive pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing.						
Unusual Fire & Explosion Hazards: Toxic fumes, gases, or vapors may evolve on burning. Vapors may be heavier than air and may travel along the ground to a distant ignition source and flash back. Oil soaked rags can cause spontaneous combustions if not handled properly. Before disposal, wash rags with soap and water and dry in a well ventilated area.						
SECTION 5 - REACTIVITY HAZARD DATA						
STABILITY	<input checked="" type="checkbox"/> STABLE	<input type="checkbox"/> UNSTABLE	Hazardous Decomposition <input type="checkbox"/> WILL <input checked="" type="checkbox"/> WILL NOT OCCUR			
Conditions to Avoid: None						
Incompatibility (Mat. to avoid): Strong oxidizers and Nitrates. The addition of Nitrates to the product can cause the formation of nitroamines.						
Hazardous Decomposition Products: Oxides of carbon, ammonia, nitrogen oxides, aldehydes and ketones						
Conditions to Avoid: None						
SECTION 6 - HEALTH HAZARD DATA						
Threshold Limit Value and Sources: None currently established by OSHA or ACGIH.						
Acute Effects of Overexposure:						
Ingestion:	Nausea, diarrhea, gastrointestinal irritation, abdominal discomfort					
Eye Contact:	Severe eye irritation with tearing, reddening and swelling of the eye and surrounding tissues					
Skin Contact:	Prolonged and repeated contact with the skin may cause irritation and redness. Wear clothing that is wetted with this material may cause severe irritation and discomfort.					
Inhalation:	May cause irritation of the upper respiratory system, nausea, headache and drowsiness..					
CHRONIC EFFECTS OF OVEREXPOSURE: Overexposure to aromatic solvents may cause destruction of red blood cells with anemia, fever, jaundice, kidney and liver damage.						
Emergency and First Aid Procedures:						
Swallowing:	Do not induce vomiting. Rinse mouth with water. Dilute stomach contents by drinking water. If vomiting occurs spontaneously keep head below hips to prevent aspiration into lungs. Seek medical attention immediately.					
Skin:	Wash skin thoroughly with soap and water. Discard contaminated clothing and shoes. Seek medical attention immediately.					
Inhalation:	Remove victim to fresh air. If breathing is labored administer oxygen. If breathing has stopped start artificial respiration immediately.					
Eyes:	Flush eyes with clear, cool, clean water for 15 minutes while holding eyelids apart to ensure flushing of entire surface of the eye. Seek medical attention immediately					
SECTION 7 – SPILL OR LEAK PROCEDURES						
Environmental Impact: Large spills of this material that release the reportable quantity must be immediately reported to the National Response Center at 202-267-2675. If this material is spilled into a waterway or watercourse treat as an oil spill and immediately call the Coast Guard Toll Free Number (800) 424-8802.						
Procedures To Be Taken if Material Is Released or Spilled: Evacuate all non-essential personnel, eliminate ignition sources and wear protective equipment. Shut off source of the leak only if safe to do so. Contain spill. Recover free product. To clean up residue, flush sparingly with water or use absorbent material. Avoid runoff to ground water. Surface waters and sewers. If required notify local. State and federal authorities.						
Waste Disposal Method: Dispose of at an approved waste or disposal site facility in accordance with all applicable federal, state and local laws and regulations. This product is considered to be an RCRA hazardous waste due to its flammability D001						

SECTION 8 – SPECIAL PROTECTION INFORMATION	
Respiratory Protection:	Local exhaust or general ventilation
Eye Protection:	Chemical type goggles or face shield.
Protective Clothing:	Oil and solvent impervious gloves. Do not wear rings, watches or similar apparel that could entrap the material and cause skin irritation.
SECTION 9 – SPECIAL PRECAUTIONS	
Precautions To Be Taken In Handling and Storage: Do not store near heat, spark, flame or strong oxidizers. Keep containers closed when not in use. Avoid inhalation of mists and vapors. Do not get on skin, eyes or clothing. Keep containers closed when not in use.	
Special Comments: Avoid prolonged contact with skin. Wash thoroughly with soap and water before eating, drinking, smoking or using toilet facilities.	
SECTION 10 – ADDITIONAL HEALTH AND TOXICOLOGICAL DATA	
HMIS & NFPA Ratings: Health = 2 Fire = 2 Reactivity = 0	
This product contains 6.83% Ethylbenzene CAS # 100-41-4 which is listed in the International Agency for Cancer Research Monographs as possibly carcinogenic to humans (Group 2B) This IRAC Classification is based upon limited evidence of carcinogenicity to animals and inadequate evidence of carcinogenicity to humans.	
This product contains 6.83% of Ethylbenzene CAS #100-41-4 which is found on the State of California's Proposition 65 List for chemicals classified as potential reproductive or cancer causing agent.	
For SARA Title III Information: see the next page	
All components of this product are on the US TSCA Inventory List and are in compliance with the Canadian Environmental Protection Act and are present on the Domestic Substances List.	
DOT Proper Shipping Name: Non-Bulk: – UN1993, Flammable Liquids, N.O.S. (Petroleum Distillates, Xylene, Ethylbenzene,), 3, PGIII, Limited Quantity	
IMDG and IATA Description: 5 gallon pails, 30 and 55 gallon drums: UN1993, Flammable Liquids, N.O.S. (Petroleum Distillates, Xylene, Ethylbenzene), 3, PGIII, (Flash Point 57°C, PMCC), Limited Quantity	

SARA Title III Information

I. Section 302/304 Extremely Hazardous

Component	CAS#	%	TPQ	RQ (lbs.)	TPQ (gal*)	RQ (gal*)
None						

II. CERCLA Section 102(a) & 302.4 Hazardous Substance & Section 313 Toxic Chemical

Component	CAS#	%	RQ (lbs.)	RQ (gals.)
Xylene	1330-20-7	0-5.6	100	231
Ethylbenzene	100-41-4	6.83	1000	1,913
Naphthalene	91-20-3	0.646	100	2,023

Section 313 Chemicals

Component	CAS#	%
Xylene	1330-20-7	0-22.12
Ethylbenzene	100-41-4	4.81
Naphthalene	91-20-3	0.153

*Product RQ for Stationary Source to release Regulatory Requirement RQ as specified by CERCLA.

III. Title III Section 311 Hazard Categorization

Acute	Chronic	Fire	Pressure	Reactivity
X	X	X		

Although the information and recommendations set forth herein (hereafter referred to as information) are presented in good faith and believed to be accurate and factual as of the date hereof, Schaeffer Mfg. Company makes no representation as to the completeness or accuracy thereof. Information is supplied upon the condition that the person receiving the same will make their own determination as to its safety and suitability for their purposes prior to use. In no event will Schaeffer Mfg. Company be responsible for damages of any natures whatsoever resulting from the use or reliance upon information. **No representation or warranty, either expressed or implied, of merchantability or fitness for a particular purpose is made with respect to information of the product to which the information refers.**