

MATERIAL SAFETY DATA SHEET

Manufacturer: Schaeffer Mfg. Company		Emergency Response Number: 314-865-4105 (24 hr Emergency Response) or 800-325-9962				
Address: 102 Barton Street						
Address: St. Louis, MO 63104						
SECTION 1 – PRODUCT INFORMATION						
Chemical Family: Petroleum Hydrocarbons			Trade Name: #137ND Diesel Treat 2000 Ultra Low Sulfur Diesel			
Formula: Proprietary Mixture						
SECTION 2 – HAZARDOUS INGREDIENTS						
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES	CAS Number	%	Exposure Limits			
			TVL		PEL	
			ppm	mg/m ³	ppm	mg/m ³
Amines, polyethylene poly-reaction products with succinic anhydride isobutylene derivatives	84605-20-9	20-30	NE		NE	
Xylene	1330-20-7	0.85-1.44	434	100	435	
Light Aromatic Solvent Naphtha	64742-95-6	0.8-2	100		NE	
2-Ethyl Hexyl Nitrate	27247-96-7	30-40	8			
Petroleum Distillates	64742-47-8	15-20	200			
Proprietary polymers	Mixture	2-5	NE		NE	
Cumene	98-82-8	0.4-0.581	50	246	50	245
1,2,4 Trimethylbenzene	95-82-6	.055-6.57	25		25	
Heavy Aromatic Solvent Naphtha	64742-94-5	7-21	NE		NE	
Ethylbenzene	100-41-4	<1.7	100	434	100	435
Naphthalene	91-20-3	0.17 – 2.2	25		25	
Benzene	71-43-2	0.00021	10	32	10	
1,3,5 Trimethylbenzene	108-67-8	0.02-0.098	25		NE	
2-Butoxyethanol	111-76-2	5-10	NE		NE	
Trimethylbenzene	25551-13-7	0.235-1.15	25	NE	25	NE
Section 3 – PHYSICAL DATA						
Boiling Point:	300°F/148.8°C		Specific Gravity:		0.9234 - 0.9254	
Vapor Pressure (mm, Hg):	<.1		% Volatile:		<15	
Vapor Density (Air = 1):	Not Determined		Evaporation Rate: (=1)		Not Determined	
Solubility in Water:	Disperses		pH:		Not Applicable	
Appearance and Odor: Dark color, slight aromatic odor.						
SECTION 4 – FIRE AND EXPLOSION HAZARD DATA						
Flash Point (Method) °F/°C: 135°-144°F/57°-62°C PMCC			Flammability Limits UEL & LEL ----Not Determined			
Extinguishing Media: Carbon dioxide foam, dry chemical foam, sand, earth, waterfog.						
Special Fire Fighting Procedures: For fires involving this material, do not enter any enclosed or confined space without protective equipment including self-contained breathing apparatus. Cool exposed containers with waterspray. Avoid breathing fumes.						
Unusual Fire & Explosion Hazards: Vapors may be heavier than air and travel along the ground to a distant ignition source and flash back. Containers may rupture upon heating. The 2-Ethyl Hexyl Nitrate contained in this product may undergo a self-accelerating exothermic reaction if the product is heated above 212°F/100°C.						
SECTION 5 - REACTIVITY HAZARD DATA						
STABILITY	<input checked="" type="checkbox"/> STABLE <input type="checkbox"/> UNSTABLE		Hazardous Decomposition <input type="checkbox"/> WILL <input checked="" type="checkbox"/> WILL NOT OCCUR			
Conditions to Avoid: High heat, high energy ignition sources						
Incompatibility (Mat. to avoid): Strong oxidizing agents, amines, phenols, halogen compounds.						
Hazardous Decomposition Products: Oxides of carbon and nitrogen and by-products of incomplete combustion.						
Conditions to Avoid: None.						
SECTION 6 - HEALTH HAZARD DATA						
Threshold Limit Value and Sources: None Established.						
Acute Effects of Overexposure:						
Ingestion:	Nausea, abdominal discomfort, diarrhea.					
Eye Contact:	Liquid contact produces severe irritation to the eyes.					
Skin Contact:	Prolonged and repeated skin contact may cause redness, severe irritation and defatting of skin. Product may be absorbed though skin.					
Inhalation:	Inhalation of vapors can cause headache, dizziness, nausea, or decreased blood pressure..					
CHRONIC EFFECTS OF OVEREXPOSURE: Repeated overexposure can cause liver and kidney damage.						
Emergency and First Aid Procedures:						
Swallowing:	If a large amount of this material is swallowed give a large amount of water to drink. Do not induce vomiting. Seek medical attention immediately.					
Skin:	Remove contaminated clothing. Wash skin thoroughly with soap and water.					
Inhalation:	Remove victim to fresh air. If breathing has stopped start artificial respiration immediately.					
Eyes:	Flush eyes with clear, cool, clean water for 15 minutes. Seek medical attention immediately.					
SECTION 7 – SPILL OR LEAK PROCEDURES						
Environmental Impact: This material is not expected to present any environmental problems other than those associated with oil spills. If spilled into a watercourse, call the Coast Guard Toll Free No. 800-424-8802.						
Procedures To Be Taken If Material Is Released or Spilled: Eliminate all sources of ignition. Absorb spills with absorbent clay. Ventilate confined spaces. Keep out of sewers and watercourses.						
Waste Disposal Method: Dispose of at an approved waste or disposal site facility in accordance with all applicable federal, state and local laws and regulations. This product is expected to be an RCRA hazardous waste due to its reactivity and presence of Benzene D018						

SECTION 8 – SPECIAL PROTECTION INFORMATION	
Respiratory Protection:	None required under ordinary conditions of use. Use NIOSH/MSHA approved full face respirator with an organic cartridge if the recommended exposure limit is exceeded or when working with this material in a confined space.
Ventilation:	Use explosion proof ventilation to control vapor concentration.
Eye Protection:	Chemical resistant goggles or full face shield.
Protective Clothing:	Viton or Nitrile gloves. Wear long sleeve shirt or chemical protective suit and neoprene boots.
SECTION 9 – SPECIAL PRECAUTIONS	
Precautions To Be Taken In Handling and Storage: Do not store near heat, spark, flame or strong oxidizers. Keep containers closed when not in use. Properly bond and ground containers and transferring equipment when transferring this product to different containers.	
Special Comments: This product is a combustible liquid. Avoid breathing vapors. Avoid prolonged or repeated skin contact. Remove contaminated shoes and clothing, launder before reuse. Throw away shoes. Wash skin thoroughly with soap and water after handling. Keep away from food and feed products	
SECTION 10 – ADDITIONAL HEALTH AND TOXICOLOGICAL DATA	
HMIS & NFPA Ratings: Health = 2 Fire = 2 Reactivity = 1	
Contaminated clothing should be disposed of properly and/or decontaminated before reuse. Under no circumstance should vomiting be induced. Vomiting can cause aspiration of the product into the lungs. If aspirated into the lungs, chemical pneumonia, which may cause death in spite of treatment with oxygen and antibiotics, may occur.	
This product contains 0.17-2.2% of Naphthalene CAS #91-20-3, 0.0021% of Benzene CAS # 71-43-2 , and <1.7% of Ethylbenzene CAS# 100-41-4 which are chemicals found on the National Toxicology Programs Annual Reports, International Agency for Cancer Research's Monographs or OSHA's Subpart Z list as suspected human cancer causing agents.	
This product contains 0.17-2.2% of Naphthalene CAS #91-20-3, 0.00021% of Benzene CAS # 71-43-2 , and <7.1% of Ethylbenzene CAS# 100-41-4 and 0.029-0.29% which are chemicals know to the State of California to cause cancer and/or birth defects.	
For SARA Title III Information, see next page.	
This product is an IRC (ignitable, corrosive, reactive) substance under CERCLA. If 36 gallons of the material is spilled which will release 100lbs. of 2-Ethyl Hexyl Nitrate into the environment and unless the material is cleaned up immediately for reprocessing, recycling or reuse this may trigger the reporting requirements of CERCLA Section 103.	
All of the ingredients of this product are on the US TSCA Inventory list and are in compliance with the Canadian Environmental Protection Act and are present on the Domestic Substance List.	
DOT Shipping Name 5 gallon pails, 30 gallon drums and 55gallon drums: UN1993, Flammable Liquids, N.O.S., (Petroleum Distillates, Heavy Aromatic Naphtha, 2-Ethylhexyl Nitrate, 2-Butoxyethanol),3,PG III	
DOT Shipping Name 4x1 gallon cases: UN1993, Flammable Liquids, N.O.S., (Petroleum Distillates, Heavy Aromatic Naphtha, 2-Ethylhexyl Nitrate, 2-Butoxyethanol),3,PG III, Limited Quantity	
DOT Shipping Name: Bulk: 275 and 330 gallon IBC: DOT Shipping Name 5 gallon pails, 30 gallon drums and 55gallon drums: UN1993, Flammable Liquids, N.O.S., (Petroleum Distillates, Heavy Aromatic Naphtha, 2-Ethylhexyl Nitrate, 2-Butoxyethanol),3,PG III, Marine Pollutant, (2-Ethylhexyl Nitrate, Naphthalene, 1,2,4 Trimethylbenzene)	
DOT Shipping Name: Bulk: >500 gallons: DOT Shipping Name 5 gallon pails, 30 gallon drums and 55gallon drums: UN1993, Flammable Liquids, N.O.S., (Petroleum Distillates, Heavy Aromatic Naphtha, 2-Ethylhexyl Nitrate, 2-Butoxyethanol),3,PG III,RQ,(Naphthalene, Xylene), Marine Pollutant, (2-Ethylhexyl Nitrate, Naphthalene, 1,2,4 Trimethylbenzene)	
IMDG Shipping Name: 5 gallon pails, 30 gallon drums and 55gallon drums: UN1993, Flammable Liquids, N.O.S., (Petroleum Distillates, Heavy Aromatic Naphtha, 2-Ethylhexyl Nitrate, 2-Butoxyethanol),3,PG III, Marine Pollutant, (2-Ethylhexyl Nitrate, Naphthalene, 1,2,4 Trimethylbenzene)	
IMDG Shipping Name: 4X1 gallon cases: UN1993, Flammable Liquids, N.O.S., (Petroleum Distillates, Heavy Aromatic Naphtha, 2-Ethylhexyl Nitrate, 2-Butoxyethanol),3,PG III, Marine Pollutant, (2-Ethylhexyl Nitrate, Naphthalene, 1,2,4 Trimethylbenzene)	

SARA Title III Information

I. Section 302/304 Extremely Hazardous

Component	CAS#	%	TPQ	RQ (lbs.)	TPQ (gal*)	RQ (gal*)
Benzene	71-43-2	0.00021		10		613,497

II. CERCLA Section 102(a) & 302.4 Hazardous Substance & Section 313 Toxic Chemical

Component	CAS#	%	RQ (lbs.)	RQ (gals.)
Benzene	71-43-2	0.00021	10	613,497
Xylene	1330-20-7	0.85-1.44	100	898
Cumene	98-82-6	0.4-0.581	5000	111,677
Ethylbenzene	100-41-4	1.7	1000	7,575
Naphthalene	91-20-3	0.17-2.2	100	585

Section 313 Chemicals

Component	CAS#	%
2-Butoxyethanol	111-76-2	5-10
Benzene	71-43-2	0.00021
Xylene	1330-20-7	0.85-1.44
Cumene	98-82-6	0.4-0.581
Ethylbenzene	100-41-4	1.7
Naphthalene	91-20-3	0.17-2.2

*Product RQ for Stationary Source to release Regulatory Requirement RQ as specified by CERCLA.

III. Title III Section 311 Hazard Categorization

Acute	Chronic	Fire	Pressure	Reactivity
X	X	X		X

Although the information and recommendations set forth herein (hereafter referred to as information) are presented in good faith and believed to be accurate and factual as of the date hereof, Schaeffer Mfg. Company makes no representation as to the completeness or accuracy thereof. Information is supplied upon the condition that the person receiving the same will make their own determination as to its safety and suitability for their purposes prior to use. In no event will Schaeffer Mfg. Company be responsible for damages of any natures whatsoever resulting from the use or reliance upon information. **No representation or warranty, either expressed or implied, of merchantability or fitness for a particular purpose is made with respect to information of the product to which the information refers.**