



TECHNICAL DATA

102 Barton Street, St. Louis MO 63104
 Ph: 800-325-9962 / Fax: 314-865-4107
 www.schaefferoil.com



266LV CITROL® LOW VOC (Spray)

Citrol® Low VOC is a biodegradable, environmentally safe, water soluble, heavy duty, organic citrus base, solvent cleaner and degreaser. It is designed for use in almost any industrial, transportation or general plant maintenance operations as a replacement for hazardous, environmentally unacceptable, aliphatic, aromatic, chlorinated, fluorocarbon, alkaline, acidic or petroleum solvent base cleaners and degreasers. Citrol® Low VOC's formulation does not contain any unacceptable petroleum distillate, petroleum hydrocarbon, chlorinated or chlorofluorocarbon type solvents, thus making the product environmentally acceptable for use.

Citrol® Low VOC was developed to comply with Volatile Organic Compound (VOC) regulations and is VOC compliant in all 50 states.

Citrol® Low VOC is specially formulated from a combination of organic citrus-based solvents and a multi-component surfactant-emulsifier system. This unique combination provides Citrol® Low VOC with the ability, when mixed with water or used straight, to rapidly penetrate and lift various soils, dirt, inks, petroleum, animal, and vegetable-based oils, fats and greases so that they can be easily removed by water rinsing.

INDUSTRIAL PLANT DEGREASER	To degrease mill stands, plant machinery, forklifts, conveyors, oil cellars, tar pumps, and valves.
INDUSTRIAL CLEANER	To clean floors, walls, production machinery, and mobile equipment.
IN THE SHOP	To degrease engines, transmissions, motors, housings, parts, floors, walls, and to remove road tar and grime from trucks, dozers and tractors.
WASTE TREATMENT PLANTS	To degrease, clean and deodorize lift stations, wet wells and walls, catwalks, bar screens, sump pumps, scum pits and troughs, transfer pipes and equipment.
MINING OPERATIONS	To degrease and remove open gear lubes, dirt and grime from dipper sticks, house rails and rollers, underground equipment and mobile equipment.

CAUTION: Prolonged immersion with Citrol® Low VOC may attack some plastics, aluminum, and painted surfaces. Spot test before using.

VOC Regulations:
 Aerosol product meets VOC requirements in all 50 states.

TYPICAL PROPERTIES

pH	10-12
Flash Point °F/°C PMCC (ASTM D93)	147°/63.9°
Specific Gravity @ 60°F (ASTM D4052)	1.029
Solubility	Complete solubility in water
Rinsability	Excellent with water